

## **1350KW** Packaged Boiler Plant

**Specification Sheet** 





## © 0808 163 5182

WWW.IDEALHEATSOLUTIONS.CO.UK

## **1350KW** Packaged Boiler Plant



Maximum Output:	1350kW Gas or Oil
Boiler:	Viessmann
Burner:	Oil: Riello RL130 Gas: Riello RS130
Pumps:	Grundfos TPD 80/150 Twin Head
Temperature Range:	Flow: 80 (90max) Return 70 (60min)
LPHW Connections:	DN100 (DN125 Possible)
Electrical:	32 amp phase 3
Gas Connection:	-
Water Connection:	15mm
Flow Rate:	16.6 kg/s and 120kPA (both pumps can run at 33.2kg/s)
Dimensions (LxWxH):	6058mm length, 2438mm width and 2591mm height (flue size: 400mm ID)
Weight:	6 tonnes (approx.)
Pressurisation Plant:	Included (800L expansion)
Telemetry:	Trend IQ4 controller with GSM modem reporting
Power Consumption:	-
Variable Temperature:	Yes
Noise:	75dBA
Handling Options:	HIAB
HWS Connection:	DN40
HWS Flow Rate:	1 Kg/s
Max HWS Temperature:	60°C
Maximum Static:	6 BAR
CWS Connection:	DN40

Bespoke options are available - call us today!



## © 0808 163 5182

WWW.IDEALHEATSOLUTIONS.CO.UK